






## 8" 70/25V Ceiling Tile Speaker



Support Rail Crossbar  
(For use within 2' x 4' tile space only)



Rear View of Speaker

### SP-CT8/T

Speco Technologies' new ceiling tile speaker is the perfect solution for commercial sound applications that require speed of installation, aesthetics and superior sound performance.

With the SP-CT8/T, installation is lightning quick and easy requiring only the connecting of speaker wire to the unit's push button terminals, then selecting the proper wattage setting on the transformer dial and laying the speaker in an established drop-ceiling.

Countless time, and money, is saved by the efficient installation-friendly design of this speaker that eliminates the labor-intensive task of cutting mounting holes in ceiling tiles usually required for standard speaker installation.

The speaker's smooth, vent-facade design blends in seamlessly with any commercial drop-ceiling environment and provides an ample gateway for wide sound dispersion. The visual design is matched by the high performance of the SP-CT8/T's flat frequency curve and wide response range.

Made of durable components and furnished complete with a support crossbar rail, the SP-CT8/T will provide countless years of reliability and sound performance.

### Specifications

Woofers	8" Polypropylene woofer with rubber surround
Tweeter	3/4" Mylar dome tweeter
Frequency Response	50Hz-20kHz
Max Power	30 Watts RMS/ 60 Watts Max
Sensitivity	90 +/- 3 dB
Impedance	8 ohms
Selector Switch	70/25 Volt
Transformer Settings	20, 10, 5, 2.5, 1.25 and 8 ohms
Dimensions	23 " W x 23 " H x 6" D
Weight	7.1 lbs.
Accessories	2' Drop-ceiling crossbar rail included

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: [www.specotech.com](http://www.specotech.com)  
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880

SP-CT8/T